



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



## LEGRAND SET PRIZE 19" PDU LCSÂ3 - 1 U - 6 X 2P+E - GERMAN **STANDARD - CU AMMETER**

Caracteristici tehnice

19" Basic PDU with ammeter

Measure Consum to provide better installation management: balancing circuits, displaying available capacity, preventing overloads and Putere failures

Measure total PDU current

Rotating display to ensure a perfect reading whatever the PDU mounting direction is (horizontal, vertical with top or bottom Tensiune de alimentare input) German standard

3 m Tensiune de alimentare cord with 16 A 2P+E French/German plug 6 outlets

Caracteristici generale

Legrand cabling system LCS<sup>3</sup> energy distribution - 1U Basic Putere Distribution Units

To provide  $\sim$  electric Putere for IT equipment in 19" enclosures 230 V - 50/60 Hz Tensiune de alimentare

1U aluminium profile

End cap with metallic brackets and cable holder shape Quick fixing (no screws) on 19" fixing centers. Can also be installed vertically by

reverting the brackets (no screws) 2P+E outlets:

C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection. Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19)

French, German and British standard outlets are equipped with safety shutters French and German standard outlets are inclined at 55°

Black module (outlets and functions) Pret: 0,00 lei (TVA inclus)

 $\label{lem:decomposition} \textbf{Detalii online:} \ \text{https://www.materialeelectrice.ro/set-prize-} 19-pdu-lcs3-1-u-6-x-2p-e-german-standard-cu-ammeter-221761$