



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD IBAN: RO34BRDE441SV13182234410



LEGRAND 2-WIRE SENZOR DE MISCARE MOSAIC - CUOUT NEUTRAL - CUOUT OVERRIDE - ALU

Caracteristici tehnice

2-wire motion sensors, without neutral

IR detection

Accepted Putere by lamp type:

LEDs: 3 to 100 W

compact fluorescent: 3 to 100 W

LED's, CFLs, Halogen, fluo tubes with ferromagnetic or electronic transformer: 3 to 250

halogen 230 V, incandescent: 3 to 250 W For LED and compact fluorescent lamps

If several sensors are installed on the same circuit, the minimum load changes: refer to

the technical sheet

Possibility to install up to 3 sensors in parallel

Time delay setting from 10 s to 10 min Light level threshold setting from 5 lux to 1275 lux

Standby Consum: 0.2 W Sensor without override

Alu

Caracteristici generale Mosaic™ Programme mechanisms - motion and presence sensors All sensors are compatible with any lamp - Detection field: 120°

Detection range: 8 m
Recommended installation height: 1.20 m

Integrated self-protection against overloads and short-circuits.

2 module

Pret: 0,00 lei (TVA inclus)

 $\label{lem:decomposition} \textbf{Detalii online:} \ https://www.materialeelectrice.ro/2-wire-senzor-de-miscare-mosaic-cuout-neutral-cuout-override-alu-222223$