

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**LEGRAND AUTOTEST/ADRESSABLE LUMINAIRES U34 LED - 1H  
DURATION CU OPAL DIFFUSER - 250 LM**

**Caracteristici tehnice**

Autotest and addressable luminaires - Maintained/Non-maintained (M/NM)  
Autotest/addressable luminaires incorporate an automatic self-testing system  
Tests result is visible on 2 signalling LEDs (green-OK and yellow-defective)  
Addressable function is activated by setting an ID on each luminaire with infrared  
configuration tool (Cat.No. 0 626 10) and wiring a complementary BUS line  
Operating state of all addressable luminaires can be centralized by the control interface  
(Cat. No. 0 626 00) and monitored on a local touch screen controller (Cat.No 0 626 01),  
or with the building's plan on Legrand Vision System (LVS2) PC software Cat.No 0 626  
02

1 h duration with transparent diffuser

250 lm - 1h (LEDs)

**Caracteristici generale**

U34LED environment friendly - indoor self-contained emergency lighting luminaires LED

LED Maintained/Non-maintained units

High Putere LEDs with specially designed lenses optimizing the lighting distribution

IP 42 - IK 07 - Class II

Tensiune de alimentare: 230 V  $\pm$  10% - 50/60 Hz

Very low Consum switching Tensiune de alimentare - Fully recyclable after removing

Environment friendly Ni-MH batteries

Removable plug-in plate to ease installation and maintenance

Automatic terminals with high capacity: 2 x 2.5 mm<sup>2</sup>

Charge monitor with a green LED

Can be equipped with metallic protection grids Cat.Nos 0 626 92/93

Pret: 958,23 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/autotest-adressable-luminaires-u34-led-1h-duration-cu-opal-diffuser-250-lm-222798>