

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND COMMUNICATION INTERFACE CX³ PENTRU RS 485 /
RAIL BUS CONVERSION - 1 MODULE**

Caracteristici tehnice

Communication interfaces

RS485 / CX³ energy management system

RS485 / CX³ energy management system conversion

Consum: 0.344 W - 28.7 mA (12 V =)

Numar de module : 1

Caracteristici generale

CX³ energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 711,41 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/communication-interface-cx3-pentru-rs-485-rail-bus-conversion-1-module-224233>