


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND CONECTOR PENTRU CONDUCTORI - NYLBLOC AUTO -
PENTRU 3 WIRES - 24 A - 450 V~**

Caracteristici tehnice
Screwless connection terminals - Nylbloc auto
No tool direct connection after simple stripping of copper conductors
Test socket for tester screwdriver or test tip Cat.No 0 394 45 for IP 2X test or O4 mm tip
on Nylbloc auto terminals
Conform to EN 60998-2-2
For rigid cable from 0.75 to 2.5 mm²
Stripping Lungime: 11 mm
Connection by separate crimping blades. Transparent base providing full visibility of the
connections
Colour code to identify products
Duplex marking possible on 3, 5 and 8-wire terminals
Max. intensity: 24 A
Insulating Tensiune: 450 V~
Orange terminal for 3 wires
Caracteristici generale
Nylbloc™ auto - screwless connection terminals
Pret: 2,15 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/conector-pentru-conductori-nylbloc-auto-pentru-3-wires-24-a-450-v-224257>