

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND CONNECTION STRIP NYLBLOC - CAPACITY 10 MM² -
MAX. CURRENT 57 A - NEGRU**

Caracteristici tehnice
Nylbloc connection strips
12 elements with captive screws
Supplied with screws undone
Flame retardant polypropylene (- 25 °C to + 100 °C)
Ambient temperature from - 25 °C to + 55 °C (T 55)
Conform to EN 60998-2-1 and EN 60664-1
Self-extinguishing to EN 60695-2-11 at 850
Insulation Tensiune: 250 V according to EN 60 998-2-1
Use at 400 V integrated in a series of products that comply with the requirements of EN 60664-1, pollution degree 2, overload category III
Black
Rated capacity: : 10 mm²
Hole O : : 4.5 mm
Max current : : 57 A
Caracteristici generale
Nylbloc™ - connection strips and connectors without screws
Pret: 10,15 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/connection-strip-nylbloc-capacity-10-mm2-max-current-57-a-negru-224314>