


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><b><u>LEGRAND CONNECTION STRIP NYLBLOC - CAPACITY 2.5 MM<sup>2</sup> - MAX. CURRENT 24 A - NEGRU</u></b></p> <p>Caracteristici tehnice Nylbloc connection strips 12 elements with captive screws Supplied with screws undone Flame retardant polypropylene (- 25 °C to + 100 °C) Ambient temperature from - 25 °C to + 55 °C (T 55) Conform to EN 60998-2-1 and EN 60664-1 Self-extinguishing to EN 60695-2-11 at 850 Insulation Tensiune: 250 V according to EN 60 998-2-1 Use at 400 V integrated in a series of products that comply with the requirements of EN 60664-1, pollution degree 2, overload category III Black Rated capacity: : 2.5 mm<sup>2</sup> Hole O : : 2.5 mm Max current : : 24 A Caracteristici generale Nylbloc™ - connection strips and connectors without screws Pret: 6,03 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/connection-strip-nylbloc-capacity-2-5-mm2-max-current-24-a-negru-224318">https://www.materialelectrice.ro/connection-strip-nylbloc-capacity-2-5-mm2-max-current-24-a-negru-224318</a></p>
---	---