



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410





Caracteristici tehnice

Convertible UPS with batteries

Single phase

The stated backup time in minutes is estimated and may vary according to the load

characteristics, operating conditions and environment Nominal Putere: : 1000 VA

Active Putere: : 900 W Backup time: : 9 min Weight: : 16 kg

Caracteristici generale

DAKER DK PLUS - On-line double conversion UPS (rack/tower) - single phase and three

phase VFI

The main parameters of the UPS, including the battery charge level and faults, are

displayed on the LCD screen on the front panel

The integrated communication software not only controls the UPS and its switch-off if there is a malfunction, and enables the user to test the main functions remotely, communicate via SNMP/Internet/network adaptor and access the functions of the UPS via the Internet, but can also send the user an SMS if specific events occur

The internal extension connector enables aWEB/SNMP card or a relay interface to be installed which provides insulated contacts for applications on industrial control panels

or remote alarm panels

If there is an electronic fault, overload, overheating or for scheduled maintenance operations, the automatic or manual (optional) bypass ensures continuity of the Tensiune de alimentare for critical loads. A bypass switch is available for maintenance

Pret: 3 220,17 lei (TVA inclus)

 $\label{lem:deconvertible} \textbf{Detalii online:} \ https://www.materialeelectrice.ro/daker-dk-plus-convertible-ups-cu-battery-single-phase-vfi-1000-va-900-w-225156$