

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND DALI LIGHTING MANAGEMENT SENSOR - 360° IR AND
ULTRASONIC - RANGE ~ 8 M**

Caracteristici tehnice
DALI lighting management sensors
Check presence and light level continuously, switch off when there is sufficient natural light
Manual switch-on and manual or automatic switch-off (factory setting)
Configuration tool Cat.No 0 882 30
Version for work areas
Suitable for meeting rooms, classrooms, open plan areas, etc.
360° infrared and ultrasonic detection, range 08 m
IP 20
Optimum distance between 2 sensors: 6 m
Fixed directly to the suspended ceiling with mounting claws (supplied) or installed in 50mm deep Batibox boxes
Connection by automatic terminals
Surface mounted on ceiling using accessory Cat.No 0 488 75
With 1 RJ 45 input
Supplied with RJ 45/BUS connector 16 V - 30 mA
Caracteristici generale
DALI management - for 1 or 2 circuits
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/dali-lighting-management-sensor-3600-ir-and-ultrasonic-range-oe-8-m-225165>