

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND DECLANSATOR ELECTRONIC MCCB + E.L.C.BS -
INTRERUPATOR GENERAL TIP USOL 250 - ICU 25 KA 400 V~ - 4P -
100 A**

Caracteristici tehnice

MCCBs with electronic earth leakage module - fixed version

Protection against overloads:

Ir adjustable from 0.4 to 1 x In

tr adjustable from 3 to 15s

Protection against short circuits:

Isd adjustable from 1.5 to 10 x Ir

tsd adjustable from 0 to 0.5s

Equipped with earth leakage module with LCD screen

Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A

Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)

Breaking capacity Icu 25 kA (400 V~)

4P

In : 100 A

Caracteristici generale

DPX³ 250 electronic release - MCCBs from 40 to 250 A

Can be mounted on rail or on plate in XL³ cabinets and enclosures

MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Supplied with fixing screws, connection plates for bars and cable lugs and insulated

shields (phase barriers)

Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid

cable and with DPX³ 160 and 250 common auxiliaries and accessories

Conform to IEC 60947-2

Pret: 5 523,42 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/declansator-electronic-mccb-e-l-c-bs-intreupator-general-tip-usol-250-icu-25-ka-400-v-4p-100-a-225234>