

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**LEGRAND INTRERUPATOR GENERAL TIP USOL ECHIPAT CU  
CONTOR + E.L.C.BS - INTRERUPATOR GENERAL TIP USOL 250 - ICU  
36 KA - 4P - 40 A**

Caracteristici tehnice  
MCCBs with energy metering central unit and electronic earth leakage module - fixed version  
Protection against overloads:  
I<sub>r</sub> adjustable from 0.4 to 1 x I<sub>n</sub>  
t<sub>r</sub> adjustable from 3 to 15s  
Protection against short circuits:  
I<sub>sd</sub> adjustable from 1.5 to 10 x I<sub>r</sub>  
t<sub>sd</sub> adjustable from 0 to 0.5s  
Equipped with earth leakage module with LCD screen  
Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A  
Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)  
Integrated energy metering central unit with LCD screen; currents, Tensiune, frequency, Putere, energy and harmonics  
Breaking capacity I<sub>cu</sub> 36 kA (400 V~)  
4P  
I<sub>n</sub> : 40 A  
Caracteristici generale  
DPX<sup>3</sup> 250 electronic release - MCCBs from 40 to 250 A  
Can be mounted on rail or on plate in XL<sup>3</sup> cabinets and enclosures  
MCCBs for switching, control isolation and protection of low Tensiune electrical lines  
Supplied with fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)  
Can be fitted with cage terminals 120 mm<sup>2</sup> max. (flexible cable) or 150 mm<sup>2</sup> max. rigid cable and with DPX<sup>3</sup> 160 and 250 common auxiliaries and accessories  
Conform to IEC 60947-2  
Pret: 9 208,65 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-tip-usol-echipat-cu-contor-e-l-c-bs-intrerupator-general-tip-usol-250-icu-36-ka-4p-40-a-228579>