

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**LEGRAND INTRERUPATOR GENERAL TIP USOL MCCB CU E.L.C.BS -  
INTRERUPATOR GENERAL TIP USOL 250 - ICU 36 KA 400 V~ - 4P -  
160 A**

**Caracteristici tehnice**

MCCBs with electronic earth leakage module - fixed version  
Thermal adjustable from 0,8 to 1 In  
Magnetic adjustable from 5 to 10 In  
Equipped with earth leakage module with LCD screen  
Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A  
Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)  
Breaking capacity Icu 36 kA (400 V~)  
4P

In : 160 A

**Caracteristici generale**

DPX<sup>3</sup> 250 thermal magnetic - MCCBs from 100 to 250 A  
Can be mounted on rail or on plate in XL<sup>3</sup> cabinets and enclosures  
MCCBs for switching, control isolation and protection of low Tensiune electrical lines  
Supplied with fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)  
Can be fitted with cage terminals 120 mm<sup>2</sup> max. (flexible cable) or 150 mm<sup>2</sup> max. rigid cable and with DPX<sup>3</sup> 160 and 250 common auxiliaries and accessories  
Conform to IEC 60947-2  
Pret: 4 488,76 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-tip-usol-mccb-cu-e-l-c-bs-intrerupator-general-tip-usol-250-icu-36-ka-400-v-4p-160-a-228708>