

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND MANUAL CALL POINT PENTRU FIRE DETECTION/ALARM
SYSTEM -CONVENTIONAL -2 NO/NC -5 A -24 V= -RAL 3000**

Caracteristici tehnice

Manual call points (MCP)

IP 30 - IK 07

Surface-mounting or Montaj incastat (IP 30)

Dimensions: 90x90x57 mm (surface-mounting with its base) or 90x90x24 mm (Montaj incastat with flush boxes for wiring devices - drilling diameter 67 mm - for 60 mm fixing centres)

Can be fitted on trunking Cat. Nos 0 104 63/64, 35x105 mm or 50x105 mm, with the universal support Cat. No 0 109 13

Call by pressing the membrane (pressure 2.5 kg) with clear display of the call position

Reset on front of device, with special key Cat. No 0 380 38 (supplied with the product)

Possibility to add an optional mechanical status indicator Cat. No 1 380 93 to provide additional signalling

Can receive a sealable cover Cat.No 0 380 97

MCP for fire detection and fire alarm systems

Conform to EN 54-11 standard

CE-CPR approved

Type A - simple action

Color of the mechanical enclosure: red RAL 3000

MCP - conventional - 2 contacts

Equipped with 2 NO/NC contacts - 5 A - 24 VDC

Second contact can be used to trigger CCTV camera (visually and recording - allows remote viewing and recording of any malicious act)

Caracteristici generale

Safety boxes 90 series - for fire detection and fire alarm system, emergency exit, extinguishing system, remote switching

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/manual-call-point-pentru-fire-detection-alarm-system-conventional-2-no-nc-5-a-24-v-ral-3000-229954>