

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND MICRANDAVES IP40 CEILING-MOUNTING DALI LIGHTING
MANAGEMENT SENSOR PENTRU 1 CIRCUIT - 360° - 9.900 GHZ**

Caracteristici tehnice

Ideal for passage areas

Microwaves IP 40 ceiling-mounting DALI Lighting Management sensor, 360°

DALI dimming sensors with a relay for switching an additional load

Maximum number of DSI or DALI ballasts: 10 (20 if the relay is disabled)

Microwaves detection, front coverage of 6 x 30 m with head tilted to 80°

Consum 0.96 W

Recommended installation height: 2.6 m

Can be installed on surface with dedicated installation box (Cat.No 0 489 64)

Microwaves admissible frequencies vary, select the correct product version according to your geographical region

9.900 GHz

Caracteristici generale

Lighting Management sensors for 1 circuit - Lighting Management sensors for passage areas with natural light

Check presence and natural light level continuously, switch off when there is sufficient natural light

Occupancy mode (automatic switch-on/off factory setting)

Can be used with push-button Cat.No 0 770 40 (or illuminated push-button Cat.No 0 770 33) for vacancy mode (manual switch-on and manual or automatic switch-off)

Precise on-site adjustment using configuration tool Cat.No 0 882 30

Adjustable time delay: 5 s to 59 min

Light level threshold adjustable from 5 to 1275 lux

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/micrandaves-ip40-ceiling-mounting-dali-lighting-management-sensor-pentru-1-circuit-3600-9-900-ghz-230479>