



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD IBAN: RO34BRDE441SV13182234410





Caracteristici tehnice Motion sensor without neutral 250 W IP 44

Compatible with any type of lamp

Detection field 120°

Detection range 8 m

Integrated self-protection against overloads and short-circuits

Screw terminals

Accepted Putere by lamp type:

LEDs 3 W to 100 W (if several sensors are installed on the same circuit, the minimum

load increases)

compact fluorescent 3 W to 100 W (if several sensors are installed on the same circuit,

the minimum load increases)

LEDs, CFLs, Halogen, fluorescent tubes with ferromagnetic or electronic ballast: 3 VA to

250 VA

230 V halogen, incandescent: 3 W to 250 W

Up to 3 sensors can be connected in parallel

Time delay setting from 10 s to 10 min. Light level threshold setting from 5 lux to 1275 lux.

Standby Consum: 0.02 W

White

Caracteristici generale Valena™ Life - IP44 devices with white cover plate

Valena In'Matic mechanisms supplied with white cover plates, weatherproof membrane

and support frames

To be equipped with plates
Supplied with mounted dust protection transparent shield
Flowpack packaging: robust protection to ensure optimum operation
Pret: 477,69 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/senzor-de-miscare-valena-life-250-wip44-cu-capac-alb-230671