

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

KVD VENTILATOR TUBULATURA 200MM 350MC/H



Ventilator metalic pentru tubulatura. Scema de montaj si domeniul de aplicare se poate vedea in poza secundara.

Material constructiv - otel
 Temperatura maxima de lucru +42 grade celsius
 Alimentare la 230V
 Grad de protectie IP X2
 Sunet 54 Db
 Turatie 1400 rotatii / minut
 Putere electrica 40W
 Flux de aer evacuat 350 mc / ora

type	unit	Ø150	Ø160	Ø200	Ø250	Ø315
Air flow	m3/h	270	280	350	600	1000
Static pressure	Pa	40	50	55	65	75
Static pressure	mmH2O	4,08	5,1	6,12	8,15	11,01
Acoustic pressure	dB(A)	50	51	54	57	62
Power supply voltage	V/Hz	230/50	230/50	230/50	230/50	230/50
Motor rotation	rpm	1400	1400	1400	1400	1400
Power	W	40	40	40	86	110
Current consumption	A	0,19	0,2	0,25	0,3	0,4
Max. Working Temp.	oC	42	42	42	42	42
Weight	kg	1,4	1,5	1,57	2,78	4,21
IP Code	IP	X2	X2	X2	X2	X2
Insulation class						

Pret: 195,90 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ventilator-tubulatura-200mm-350mc-h>