

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



KVD VENTILATOR DE PERETE 300MM 2400MC/H

Ventilator de perete.
Schema de montaj si domeniul de aplicare se poate vedea in poza secundara.
Material constructiv - otel
Temperatura maxima de lucru +70 grade celsius
Alimentare la 230V
Grad de protectie IP X4
Sunet 73 Db
Turatie 2580 rotatii / minut
Putere electrica 145W
Flux de aer evacuat 2400 mc / ora

	tubulatura	latime totala	grosime	latime intre suruburi
WOKS Ø200	212	320	70	260
WOKS Ø250	262	365	90	315
WOKS Ø300	313	430	92	380
WOKS Ø350	360	485	88	435
WOKS Ø400	408	540	100	490
WOKS Ø450	465	575	125	535
WOKS Ø500	515	655	115	615
WOKS Ø550	575	725	115	670
WOKS Ø630	650	805	125	750
WOKS Ø710	725	850	130	810
WOKS Ø800	835	970	200	910

type	unit	WOKS Ø200	WOKS Ø250	WOKS Ø300	WOKS Ø350	WOKS Ø400	WOKS Ø450	WOKS Ø500	WOKS Ø550	WOKS Ø630	WOKS Ø710
		Air flow	m ³ /h	850	1600	2400	3100	3400	4800	6000	7560
Static pressure	Pa	130	160	220	140	200	240	110	110	170	Δ130
Static pressure	mmH ₂ O	13,26	16,31	22,43	14,28	20,39	24,47				
Acoustic pressure	dB(A)	63	67	73	64	69	73	72	75	78	80
Power supply voltage	V/Hz	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50
Motor rotation	rpm	2300	2480	2580	1400	1430	1420	1300	1300	1360	Δ900
Power	W	55	90	145	140	140	250	420	550	750	Δ900
Current consumption	A	0,26	0,45	0,62	0,6	0,6	1,1	1,95	2,55	3,55	Δ1.90
Max. Working Temp.	oC	70	70	70	45	40	40	60	60	60	60
Weight	kg	2,92	3,93	4,9	6,71	8	9,51	12,80	17.20	23.20	37.80
IP Code	IP	X4	X4	X4	X4	X4	X4	X4	X4	X4	X4
Insulation class											

Pret: 555,84 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ventilator-de-perete-300mm-4000mc-h>