

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



KVD VENTILATOR DE PERETE 800MM 19000MC/H 380V

Ventilator de perete.
Schema de montaj si domeniul de aplicare se poate vedea in poza secundara.
Material constructiv - otel
Temperatura maxima de lucru +60 grade celsius
Alimentare la 380V
Grad de protectie IP X4
Sunet 82 Db
Turatie 770 rotatii / minut in stea si 920 rotatii / minut in triunghi
Putere electrica 1200W in triunghi
Flux de aer evacuat 19000 mc / ora in triunghi si 14800 in stea

	tubulatura	latime totala	grosime	latime intre suruburi
WOKS Ø200	212	320	70	260
WOKS Ø250	262	365	90	315
WOKS Ø300	313	430	92	380
WOKS Ø350	360	485	88	435
WOKS Ø400	408	540	100	490
WOKS Ø450	465	575	125	535
WOKS Ø500	515	655	115	615
WOKS Ø550	575	725	115	670
WOKS Ø630	650	805	125	750
WOKS Ø710	725	850	130	810
WOKS Ø800	835	970	200	910

type	unit	WOKS	WOKS	WOKS	WOKS	WOKS	WOKS	WOKS	WOKS	WOKS	WOKS
		Ø200	Ø250	Ø300	Ø350	Ø400	Ø450	Ø500	Ø550	Ø630	Ø710
Air flow	m3/h	850	1600	2400	3100	3400	4800	6000	7560	10080	Δ1550
Static pressure	Pa	130	160	220	140	200	240	110	110	170	Δ130
Static pressure	mmH2O	13,26	16,31	22,43	14,28	20,39	24,47				
Acoustic pressure	dB(A)	63	67	73	64	69	73	72	75	78	80
Power supply voltage	V/Hz	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50
Motor rotation	rpm	2300	2480	2580	1400	1430	1420	1300	1300	1360	Δ900
Power	W	55	90	145	140	140	250	420	550	750	Δ900
Current consumption	A	0,26	0,45	0,62	0,6	0,6	1,1	1,95	2,55	3,55	Δ1.90
Max. Working Temp.	oC	70	70	70	45	40	40	60	60	60	60
Weight	kg	2,92	3,93	4,9	6,71	8	9,51	12,80	17.20	23.20	37.80
IP Code	IP	X4	X4	X4	X4	X4	X4	X4	X4	X4	X4
Insulation class											

Pret: 3 968,85 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ventilator-de-perete-800mm-19000mc-h-380v>