

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND DESCARCATOR SPD - HIGH RISK LEVEL INSTALLATION -
T1+T2 - LIMP 25 KA/POLE - 1P+N RIGHT**

Caracteristici tehnice
SPDs for high risk level installations
SPDs for big installations with external lightning protection (LPS) and for high risk level installations according to EN/IEC 62305 standards
SPDs with plug-in module and status indicators:
Green: SPD operational
Red: plug-in module to be replaced
T1 + T2 - Iimp 25 kA/pole
Up: 1.5 kV - Uc: 350 V~
Earthing systems: TT, TNC, TNS.
Recommended MCCB: DPX³ 160 - 80 A
1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1
Numar de poli : 1P+N
Pozitie NUL : Dreapta
Itotal (10/350) : 50 kA
Remote status monitoring (FS contact) : Yes
Numar de module : 4
Caracteristici generale
Class I + II (T1+T2) low Tensiune SPDs
Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz).
SPDs compliant with EN/IEC 61643-11 standards
Recommended for main distribution boards
Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes
Pret: 2 644,22 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/descarcator-spd-high-risk-level-installation-t1-t2-limp-25-ka-pole-1p-n-right-235690>