

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



LEGRAND DESCARCATOR SPD - PROTECTION OF MAIN DISTRIBUTION BOARD -T1+T2 -LIMP 12.5 KA/POLE -3P+N LEFT

Caracteristici tehnice
 SPDs for general protection of main distribution board
 SPDs with plug-in module and status indicators:
 Green: SPD operational
 Orange: plug-in module to be replaced
 Earthing systems: TT, TNC, TNS
 T1+T2 - Iimp 12,5 kA/pole
 For general protection of big installations and protection of small installations with external lightning protection (LPS).
 Up: 1.5 kV - I_{max}: 60 kA/pole - U_c: 320 V~
 Recommended MCB: DX³ 63 A - C curve
 1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1
 Numar de poli : 3P+N
 Pozitie NUL : Stanga
 I_{total} (10/350) : 50 kA
 Remote status monitoring (FS contact) : Yes
 Numar de module : 4
 Caracteristici generale
 Class I + II (T1+T2) low Tensiune SPDs
 Protection against transient overTensiune for 230/400 V~ Putere networks (50/60 Hz).
 SPDs compliant with EN/IEC 61643-11 standards
 Recommended for main distribution boards
 Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes
 Pret: 840,47 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/descarcator-spd-protection-of-main-distribution-board-t1-t2-limp-12-5-ka-pole-3p-n-left-235707>