

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND DESCARCATOR SPD -PROTECTION OF MAIN
DISTRIBUTION BOARD -T1+T2 -LIMP 12.5 KA/POLE -1P+N RIGHT**

Caracteristici tehnice
SPDs for general protection of main distribution board
SPDs with plug-in module and status indicators:
Green: SPD operational
Orange: plug-in module to be replaced
Earthing systems: TT, TNC, TNS
T1+T2 - limp 12,5 kA/pole
For general protection of big installations and protection of small installations with external lightning protection (LPS).
Up: 1.5 kV - I_{max}: 60 kA/pole - U_c: 320 V~
Recommended MCB: DX³ 63 A - C curve
1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1
Numar de poli : 1P+N
Pozitie NUL : Dreapta
I_{total} (10/350) : 25 kA
Remote status monitoring (FS contact) : Yes
Numar de module : 2
Caracteristici generale
Class I + II (T1+T2) low Tensiune SPDs
Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz).
SPDs compliant with EN/IEC 61643-11 standards
Recommended for main distribution boards
Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes
Pret: 437,66 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/descarcator-spd-protection-of-main-distribution-board-t1-t2-limp-12-5-ka-pole-1p-n-right-235722>