


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><b><u>LEGRAND STRAIGHT LENGHT BARA CAPSULATA MS100 100A 1+1 OUTLETS - 1.5M</u></b></p> <p>Caracteristici tehnice Straight elements L : 1.5 m Outlets : 1+1 Caracteristici generale MS mini busbars - trunking components Reference standard: IEC 61439-6 Reference temperature: 40 °C Degree of Protection: IP 40/55 Thickness: 0.8 mm Dimension: 39x97mm N° of conductors: 4 with equal section 3P+N Conducting «fire retardant» in accordance with EN 60332-3 Separation between the conductors by plastic insulators reinforced with 20% glass fiber, which guarantees a degree of V1 self-extinguishing (according to UL94) and conform to the glow-wire test according to IEC 60695-2-10 Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialeelectrice.ro/straight-lenght-bara-capsulata-ms100-100a-1-1-outlets-1-5m-235888">https://www.materialeelectrice.ro/straight-lenght-bara-capsulata-ms100-100a-1-1-outlets-1-5m-235888</a></p>
---	---