


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><u>LEGRAND STRAIGHT LENGHT BARA CAPSULATA MS100 100A</u> <u>OUTLETS TO BE DEFINED IN BASE OF THE LUNGIME OF ELEMENT -</u> <u><1.5M</u></p> <p>Caracteristici tehnice Straight elements L : Outlets : Outlets to be defined in base of the Lungime of element</p> <p>Caracteristici generale MS mini busbars - trunking components Reference standard: IEC 61439-6 Reference temperature: 40 °C Degree of Protection: IP 40/55 Thickness: 0.8 mm Dimension: 39x97mm N° of conductors: 4 with equal section 3P+N Conducting «fire retardant» in accordance with EN 60332-3 Separation between the conductors by plastic insulators reinforced with 20% glass fiber, which guarantees a degree of V1 self-extinguishing (according to UL94) and conform to the glow-wire test according to IEC 60695-2-10 Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/straight-lenght-bara-capsulata-ms100-100a-outlets-to-be-defined-in-base-of-the-lungime-of-element-1-5m-235892</p>
---	--