

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

**LEGRAND STRAIGHT LENGHT MS160 160A 1+1 OUTLETS - 1.5M**



**Caracteristici tehnice**

Straight elements

L : 1.5 m

Outlets : 1+1

**Caracteristici generale**

MS mini busbars - trunking components

Reference standard: IEC 61439-6

Reference temperature: 40 °C

Degree of Protection: IP 40/55

Thickness: 0.8 mm

Dimension: 39x97mm

N° of conductors: 4 with equal section 3P+N

Conducting «fire retardant» in accordance with EN 60332-3

Separation between the conductors by plastic insulators reinforced with 20% glass fiber, which guarantees a degree of V1 self-extinguishing (according to UL94) and conform to the glow-wire test according to IEC 60695-2-10

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/straight-lenght-ms160-160a-1-1-outlets-1-5m-235894>