

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND TRANSFORMATOR DE IZOLATIE -1 PH-PRIM 230-400 VÂ±
15 V / SEC 230 V - 40 VA - SPRING**

Caracteristici tehnice

Control and circuit isolation - spring connection

Input Tensiune = 230-400 V ± 15 V~ Output Tensiune = 230 V~

Putere in VA according to IEC and CSA : 40

Putere in VA according to UL : 40

Instantaneous admissible Putere at cos φ = 0.5 : 50

Caracteristici generale

Control, safety and circuit isolation transformers - single-phase

IP 2X or XXB up to 400 VA (coupling strip not mounted) - IP XXA over 400 VA - IK 04

Conform to IEC EN 61558-2-2 and 2-4 or 2-6, UL506 and CSA C22-2-No 66

UL USA and Canada agreements

Products suitable for building equipment conforming to standards EN 61131-2, EN 60204-1 and EN 60439-1

Active parts protected by cover up to 1000 VA

Interference filtering (except Cat.Nos 0 442 16/17/18)

Direct fixing possibility on symmetrical rail up to 250 VA

Supplied with coupling strip 0 V secondary / earth up to 1000 VA (except spring connection range)

Pret: 480,05 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/transformator-de-izolatie-1-ph-prim-230-400-v-15-v-sec-230-v-40-va-spring-236715>