

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND TRANSFORMATOR DE IZOLATIE PENTRU SPITALE -3
PHASE- PRIM 400 V / SEC 230 V -OUTPUT 10 KVA**

Caracteristici tehnice

3-phase

Primary: 400 V~ + N / Secondary: 230 V~ + N

Equipped with a temperature monitoring system (bi-metal strips) for connection to a control system (optical, acoustic, etc...)

IP 21

Output : 10 kVA

Terminal primary flexible cable : 16 mm²

Terminal secondary flexible cable : 35 mm²

Caracteristici generale

Isolating transformers for hospitals

Conform to standard IEC EN 61558-2-15

The main requirements of this standard, additionally to IEC 61558-2-4, concern:
secondary/earth leakage current, limited to 0.5 mA off-load

inrush current, limited to 12 times the peak value of primary current

Electrostatic shield linked to dedicated terminal

Equipped with a temperature monitoring system, and outputs on dedicated terminals

Pret: 22 310,40 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/transformator-de-izolatie-pentru-spitale-3-phase-prim-400-v-sec-230-v-output-10-kva-236730>