

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND TUB FLEXIBIL - HIGH IMPACT - SHOCK RESISTANCE 6
JOULES - Å EXT. 16 MM**

Caracteristici tehnice
High impact with draw wire (ICTA 3422)
Material: Polyolefin additives
Halogen free
Dark grey (RAL 7024)
Impact resistance: 6 joules at - 5 °C
Min operating t°: - 5 °C
Max operating t°: + 90 °C
IK 08
Prelubricated inner surface for easy pulling of the wires
Nylon-coated steel wire puller for a better resistance to corrosion
Surface mounting not recommended outside. Suitable for prefabricated concrete
O exterior: : 16 mm
O interior: : 10.7 mm
colour of ties on coil : : blue
Caracteristici generale
Flexible conduits
Non flame propagating
Conform to standard EN/IEC 61386-22
Crush resistance: 750 Newtons
Supplied wrapped in film, the coil acts as a pay-out reel
The various diameters are identified by coloured ties
Surface-mounting or Montaj incastat
Pret: 2,75 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tub-flexibil-high-impact-shock-resistance-6-joules-oe-ext-16-mm-236880>