

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**LEGRAND TUB FLEXIBIL - HIGH IMPACT - SHOCK RESISTANCE 6  
JOULES - Å EXT. 25 MM**

Caracteristici tehnice  
High impact with draw wire (ICTA 3422)  
Material: Polyolefin additives  
Halogen free  
Dark grey (RAL 7024)  
Impact resistance: 6 joules at - 5 °C  
Min operating t°: - 5 °C  
Max operating t°: + 90 °C  
IK 08  
Prelubricated inner surface for easy pulling of the wires  
Nylon-coated steel wire puller for a better resistance to corrosion  
Surface mounting not recommended outside. Suitable for prefabricated concrete  
O exterior: : 25 mm  
O interior: : 18.3 mm  
colour of ties on coil: : green  
Caracteristici generale  
Flexible conduits  
Non flame propagating  
Conform to standard EN/IEC 61386-22  
Crush resistance: 750 Newtons  
Supplied wrapped in film, the coil acts as a pay-out reel  
The various diameters are identified by coloured ties  
Surface-mounting or Montaj incastat  
Pret: 5,13 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tub-flexibil-high-impact-shock-resistance-6-joules-oe-ext-25-mm-236882>