


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND TUB FLEXIBIL - MEDIUM IMPACT - SHOCK RESISTANCE 2
JOULES - Å EXT. 16 MM**

Caracteristici tehnice
Medium impact (ICA 3321)
Material: PVC without Pb, Sn, Cd (RoHS compliant)
Light grey (RAL 7035)
Impact resistance: 2 joules at - 5 °C
Min operating t°: - 5 °C
Max operating t°: + 60 °C
IK 07
Flush-mounted in certain cases before construction of the masonry
O exterior: : 16 mm
O interior: : 10.7 mm
colour of ties on coil: : blue
Caracteristici generale
Flexible conduits
Non flame propagating
Conform to standard EN/IEC 61386-22
Crush resistance: 750 Newtons
Supplied wrapped in film, the coil acts as a pay-out reel
The various diameters are identified by coloured ties
Surface-mounting or Montaj incastrat
Pret: 2,27 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tub-flexibil-medium-impact-shock-resistance-2-joules-oe-ext-16-mm-236887>