


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">LEGRAND TUB RIGID PREMUFAT - SHOCK RESISTANCE 2 JOULES - AA~ EXT. 25 MM</p> <p>Caracteristici tehnice Medium impact rigid conduits with integrated coupling PVC without Pb, Sn, Cd (RoHS compliant) Non flame propagating Surface-mounting or Montaj incastat Suitable for prefabricated concrete. Conforming to European standard: EN/IEC 61386-21 Crush resistance: 750 Newtons. Impact resistance: 2 joules at - 5 °C Min operating t°: - 5 °C ; Max operating t°: + 60 °C IK 07 Can be used outside Supplied wrapped in film. Light grey (RAL 7035) Lungime of tubes: 3 m O exterior : : 25 mm O interior : : 21.4 mm thickness : : 1.80 mm Caracteristici generale Rigid conduits Pret: 8,18 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/tub-rigid-premufat-shock-resistance-2-joules-oe-ext-25-mm-236895</p>
---	---