

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **PHILIPS PL-S MASTER PL-S 5W/840/2P 1CT/5X10BOX**

#### General Information

Baza elementului de fixare

G23

[ G23]

DuratÄf de viaÈ>Äf panÄf la eÈ™ ec de 10% (nom.)

6500 h

DuratÄf de viaÈ>Äf panÄf la eÈ™ ec de 50% (nom.)

10000 h

LSF (Factor de dispersie a luminii) 2.000 h nominal

99 %

LSF (Factor de dispersie a luminii) 4.000 h nominal

98 %

LSF (Factor de dispersie a luminii) 6.000 h nominal

95 %

LSF (Factor de dispersie a luminii) 8.000 h nominal

86 %

Sphere

Light Technical

Cod culoare

840

[ CCT de 4000 K]

Flux luminos (nom.)

250 lm

Flux luminos (Evaluat) (nom.)

259 lm

Denumirea culorii

Alb rece (CW)

CoordonatÄf cromaticÄf X (nom.)

0,38

CoordonatÄf cromaticÄf Y (nom.)

0,38

TemperaturÄf de culoare corelatÄf (nom.)

4000 K

Randament luminos (nominal) (nom.)

48 lm/W

Indice de redare a culorii (nom.)

80

LLMF (Factor de menÈ›inere flux luminos lampÄf) 2.000 h nominal

89 %

LLMF (Factor de menÈ›inere flux luminos lampÄf) 4.000 h nominal

83 %

LLMF (Factor de menÈ›inere flux luminos lampÄf) 6.000 h nominal

80 %

LLMF (Factor de menÈ›inere flux luminos lampÄf) 8.000 h nominal

77 %

Operating and Electrical

Putere consumatÄf (W) (Nom)

5,5 W

Curent lampÄf (nom.)

0,180 A

Temperature

TemperaturÄf de proiectare (nom.)

28 °C

Controls and Dimming

Cu reglarea intensitÄfÈ›ii luminoase

Nu

Mechanical and Housing

InformaÈ›ii bazÄf element fixare

2P

Approval and Application

Energy Efficiency Class

G

ConÈ›inut de mercur (Hg) (max.)

1,4 mg

ConÈ›inut de mercur (Hg) (nom.)

1,4 mg

Consum de energie kWh/1000 h

6 kWh

423579

Product Data

Cod complet produs

871150026048270

Nume comandÄf produs

MASTER PL-S 5W/840/2P 1CT/5X10BOX

EAN/UPC - Produs

8711500260482

Cod de comandÄf

26048270  
NumÄfrÄftor SAP - Cantitate per pachet  
1  
NumÄfrÄftor SAP - Pachete per exterior  
50  
Material SAP  
927935284011  
Greutate netÄf SAP (bucatÄf)  
22,000 g  
Cod ILCOS  
FSD-5/40/1B-I-G23  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pl-s-master-pl-s-5w-840-2p-1ct-5x10box-251928>