

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



PHILIPS PL-L MASTER PL-L XTRA 36W/840/4P 1CT/25

General Information

Baza elementului de fixare

2G11

[2G11]

DuratÄf de viaÄf panÄf la eÈ™ec de 10% (nom.)

14000 h

DuratÄf de viaÄf panÄf la eÈ™ec de 50% (nom.)

21000 h

DuratÄf de viaÄf panÄf la eÈ™ec de 50% incÄflzire prealabilÄf (nom.)

36000 h

Descriere sistem

na

[-]

LSF (Factor de dispersie a luminii) 2.000 h nominal

99 %

LSF (Factor de dispersie a luminii) 4.000 h nominal

99 %

LSF (Factor de dispersie a luminii) 6.000 h nominal

98 %

LSF (Factor de dispersie a luminii) 8.000 h nominal

97 %

LSF (Factor de dispersie a luminii) 12.000 h nominal

95 %

LSF (Factor de dispersie a luminii) 16.000 h nominal

88 %

LSF (Factor de dispersie a luminii) 20.000 h nominal

58 %

LSF (Factor de dispersie a luminii) incÄflzire prealabilÄf 2.000 h nominal

99 %

LSF (Factor de dispersie a luminii) incÄflzire prealabilÄf 4.000 h nominal

99 %

LSF (Factor de dispersie a luminii) incÄflzire prealabilÄf 6.000 h nominal

99 %

LSF (Factor de dispersie a luminii) incÄflzire prealabilÄf 8.000 h nominal

99 %

LSF (Factor de dispersie a luminii) incÄflzire prealabilÄf 16.000 h nominal

97 %

LSF (Factor de dispersie a luminii) incÄflzire prealabilÄf 20.000 h nominal

94 %

Sphere

Light Technical

Cod culoare

840

[CCT de 4000 K]

Flux luminos (nom.)

2800 lm

Flux luminos (Evaluat) (nom.)

2900 lm

Denumirea culorii

Alb rece (CW)

CoordonatÄf cromaticÄf X (nom.)

0,38

CoordonatÄf cromaticÄf Y (nom.)

0,38

TemperaturÄf de culoare corelatÄf (nom.)

4000 K

Randament luminos (nominal) (nom.)

81 lm/W

Indice de redare a culorii (nom.)

80

LLMF (Factor de menÈinere flux luminos lampÄf) 2.000 h nominal

94 %

LLMF (Factor de menÈinere flux luminos lampÄf) 4.000 h nominal

93 %

LLMF (Factor de menÈinere flux luminos lampÄf) 6.000 h nominal

92 %

LLMF (Factor de menÈinere flux luminos lampÄf) 8.000 h nominal

91 %

LLMF (Factor de menÈinere flux luminos lampÄf) 12.000 h nominal

90 %

LLMF (Factor de menÈinere flux luminos lampÄf) 16.000 h nominal

89 %

LLMF (Factor de menÈinere flux luminos lampÄf) 20.000 h nominal

88 %

Operating and Electrical

Putere consumatÄf (W) (Nom)

36,3 W

Curent lampÄf (nom.)
0,435 A
Temperature
TemperaturÄf de proiectare (nom.)
30 °C
Controls and Dimming
Cu reglarea intensitÄfE>ii luminoase
Da
Mechanical and Housing
InformaE>ii bazÄf element fixe
4P
Approval and Application
Energy Efficiency Class
G
ConE>inut de mercur (Hg) (max.)
3 mg
ConE>inut de mercur (Hg) (nom.)
3,0 mg
Consum de energie kWh/1000 h
37 kWh
423277
Product Data
Cod complet produs
871150089760240
Nume comandÄf produs
MASTER PL-L Xtra 36W/840/4P 1CT/25
EAN/UPC - Produs
8711500897602
Cod de comandÄf
89760240
NumÄfrÄftor SAP - Cantitate per pachet
1
NumÄfrÄftor SAP - Pachete per exterior
25
Material SAP
927904784014
Greutate netÄf SAP (bucatÄf)
104,000 g
Cod ILCÖS
FSD-36/40/1B-E-2G11
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pl-l-master-pl-l-xtra-36w-840-4p-1ct-25-252068>