


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p>ZALUX LAMPA LINIARA ETANSA CU FIXARE RAPIDA BHE 1.2 40-840 ETDD CS BPC HFS</p> <p>Long-lasting, compact and resistant luminaire with easy installation Single-part IP66 / IP69K extruded polycarbonate profile, up to 138lm/W and flicker free. Available wireless Bluetooth control to save energy and optimize light. PWIS-free to guarantee a perfect finish in paint shops and coating areas. Quick and safe mounting with no tools needed. Customizable end caps. Downloads Features Mechanical Profile Extruded polycarbonate with UV protection, upper part grey RAL 7035, bottom part opal End caps Injected polycarbonate Gasket PWISS-free silicone Cable entry Cable gland Fixing clips Stainless steel Operational Data Light colour 4,000 K CRI >80 Luminous flux 4,000 lm Power 29 W Efficiency 138 lm/W Sensor High frequency sensor Functional Lifetime L80 70,000 h at 25°C Fire protection PC / Flammability (UL94): V2 Glow wire test (EN 60695-2-11): 850°C Electrical Driver DALI Casambi dimmable Connection 5 pole push wire terminal block Flicker factor < 1% Intelligent control Yes Power factor > 0.95 full load Photometrical Colour consistency < 3 SDCM Dimensions Length (X) 1,213 mm Distance between springs (Xm) 800 mm Width (Y) 76 mm Height (Z) 67 mm Weight 1.8 kg Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/lampa-liniara-etansa-cu-fixare-rapida-bhe-1-2-40-840-etdd-cs-bpc-hfs-287544</p>
---	---