


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p>ZALUX LAMPA LINIARA ETANSA CU FIXARE RAPIDA BHE 69K 1.5 60-840 ET BPM 3M 5X2.5 L1</p> <p>Gas-tight, long-lasting, compact and resistant luminaire with easy installation Single-part IP66 / IP69K extruded PMMA profile, up to 138lm/W and flicker free. Gas tight: hermetically sealed against liquid and gas income. PWIS-free to guarantee a perfect finish in paint shops and coating areas. Quick and safe mounting with no tools needed. Extraordinary chemical resistance.</p> <p>Downloads Features Mechanical Profile Extruded PMMA with UV protection, upper part grey RAL 7035, bottom part opal End caps Acrylonitrile styrene acrylate (ASA) Gasket PWISS-free silicone Cable entry Cable gland with external cable Fixing clips Stainless steel</p> <p>Operational Data Light colour 4,000 K CRI >80 Luminous flux 6,000 lm Power 44 W Efficiency 135 lm/W Through wiring 5 x 2.5 mm²</p> <p>Functional Lifetime L80 70,000 Custom.U1 at 25°C Fire protection GRP and PMMA / Flammability (UL94): HB Glow wire test (EN 60695-2-11): 650°C</p> <p>Electrical Driver non dimmable Connection External cable 3m Flicker factor < 1% Power factor > 0.95 full load</p> <p>Photometrical Colour consistency < 3 SDCM</p> <p>Dimensions Length (X) 1,480 mm Distance between springs (Xm) 1,100 mm Width (Y) 76 mm Height (Z) 67 mm Weight 3.9 kg</p> <p> Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/lampa-liniara-etansa-cu-fixare-rapida-bhe-69k-1-5-60-840-et-bpm-3m-5x2-5-11-287558</p>
--	--