

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



ZALUX LAMPA LINIARA ETANSA CU FIXARE RAPIDA BSTP 1.2 40-840 ETDD BPC 5X1.5

Long-lasting, compact and resistant luminaire with easy installation
Single-part IP66 / IP69K extruded polycarbonate profile, up to 125 m/W and flicker free.
PWIS-free to guarantee a perfect finish in paint shops and coating areas.
Quick and safe mounting with no tools needed: cable gland and connector fixed to the
gear tray by a patented piece.

Customizable end caps

Downloads

Features

Mechanical

Profile Extruded polycarbonate with UV protection, upper part grey RAL 7035, bottom
part opal

End caps Injected polycarbonate

Gasket PWIS-free silicone

Cable entry Cable gland

Fixing clips Stainless steel

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 4,000 lm

Power 32 W

Efficiency 125 lm/W

Through wiring 5 x 1.5 mm²

Functional

Lifetime L80 50,000 h at 25°C

Fire protection PC / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 850°C

Electrical

Driver DALI dimmable

Connection Terminal block

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,213 mm

Distance between springs (Xm) 800 mm

Width (Y) 76 mm

Height (Z) 67 mm

Weight 2 kg

<span class="elementor-button-text"

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa-liniara-etansa-cu-fixare-rapida-bstp-1-2-40-840-etdd-bpc-5x1-5-287574>