


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">ZALUX LAMPA LINIARA TIP FIPAD DHE 1.5 100-840 ET SMC DPM IX CG 5X2.5</p> <p>Linear openable high bay Up to 170lm/W. Up to 50°C. Chemical resistant. Up to 15,000lm under request for the higher installations.</p> <p>Downloads</p> <p>Features</p> <p>Mechanical</p> <p>Housing Compressed fibreglass reinforced polyester (GRP), grey RAL 7035 Diffuser Injected PMMA with UV protection, frosted finish Gasket Polyurethane Cable entry Cable gland Closing clips Stainless steel Fixing clips Stainless steel</p> <p>Operational Data</p> <p>Light colour 4,000 K CRI >80 Luminous flux 10,000 lm Power 59 W Efficiency 170 lm/W Through wiring 5 x 2.5 mm²</p> <p>Functional</p> <p>Lifetime L80 100,000 h at 35°C Fire protection GRP and PMMA / Flammability (UL94): HB Glow wire test (EN 60695-2-11): 650°C</p> <p>Electrical</p> <p>Driver non dimmable Connection 3 pole push wire terminal block Flicker factor < 1% Power factor > 0.95 full load</p> <p>Photometrical</p> <p>Colour consistency < 3 SDCM</p> <p>Dimensions</p> <p>Length (X) 1,573 mm Distance between springs (Xm) 1,100 mm Width (Y) 101 mm Height (Z) 84 mm Weight 2.3 kg</p> <p> Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/lampa-liniara-tip-fipad-dhe-1-5-100-840-et-smc-dpm-ix-cg-5x2-5-287581</p>
---	--