


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p>ZALUX LAMPA LINIARA TIP FIPAD DHE+ 1.5 60-840 ETDD SMC DPM IX CG 5X2.5</p> <p>High performance with optional wireless Bluetooth control Up to 160lm/W and 50°C with high chemical resistance. 100,000 hours lifetime to contribute to installation profitability. With internal diffuser to avoid direct contact with LED module. Optional presence and daylight sensors to optimize the use of the light.</p> <p>Downloads</p> <p>Features</p> <p>Mechanical</p> <p>Housing Compressed fibreglass reinforced polyester (GRP), grey RAL 7035 Diffuser Injected PMMA with UV protection, frosted finish Gasket Polyurethane Cable entry Cable gland Closing clips Stainless steel Fixing clips Stainless steel</p> <p>Operational Data</p> <p>Light colour 4,000 K CRI >80 Luminous flux 6,000 lm Power 37 W Efficiency 160 lm/W Through wiring 5 x 2.5 mm²</p> <p>Functional</p> <p>Lifetime L80 100,000 h at 35°C Fire protection GRP and PMMA / Flammability (UL94): HB Glow wire test (EN 60695-2-11): 650°C</p> <p>Electrical</p> <p>Driver DALI dimmable Connection 5 pole push wire terminal block Flicker factor < 1% Power factor > 0.95 full load</p> <p>Photometrical</p> <p>Colour consistency < 3 SDCM</p> <p>Dimensions</p> <p>Length (X) 1,573 mm Distance between springs (Xm) 1,100 mm Width (Y) 101 mm Height (Z) 84 mm Weight 2.3 kg</p> <p> Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/lampa-liniara-tip-fipad-dhe-1-5-60-840-etdd-smc-dpm-ix-cg-5x2-5-287602</p>
---	--