


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p><b><u>ZALUX LAMPA LINIARA TIP FIPAD DSTP 1.5 60-840 ET PC DPC IX-U 3X1.5</u></b></p> <p>Versatile luminaire with up to 145lm/W Flicker-free for a high quality lighting. Unremovable stainless steel or plastic closing clips for enhanced safety. High impact protection and easy mounting. First-class raw materials safe against premature deterioration.</p> <p>Downloads Features Mechanical Housing Injected polycarbonate with UV protection, grey RAL 7035 Diffuser Injected polycarbonate with UV protection, frosted finish Gasket Polyurethane Cable entry Grommet Closing clips Stainless steel unremovable Fixing clips Stainless steel</p> <p>Operational Data Light colour 4,000 K CRI &gt;80 Luminous flux 6,000 lm Power 42 W Efficiency 145 lm/W Through wiring 3 x 1.5 mm<sup>2</sup></p> <p>Functional Lifetime L80 50,000 h at 25°C Fire protection PC / Flammability (UL94): V2 Glow wire test (EN 60695-2-11): 850°C</p> <p>Electrical Driver non dimmable Connection 3 pole push wire terminal block Flicker factor &lt; 1% Power factor &gt; 0.95 full load</p> <p>Photometrical Colour consistency &lt; 3 SDCM</p> <p>Dimensions Length (X) 1,573 mm Distance between springs (Xm) 1,100 mm Width (Y) 101 mm Height (Z) 84 mm Weight 2.2 kg</p> <p>&lt;span class="elementor-button-text"&gt; Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialeelectrice.ro/lampa-liniara-tip-fipad-dstp-1-5-60-840-et-pc-dpc-ix-u-3x1-5-287620">https://www.materialeelectrice.ro/lampa-liniara-tip-fipad-dstp-1-5-60-840-et-pc-dpc-ix-u-3x1-5-287620</a></p>
---	---