

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**ZALUX LAMPA LINIARA TIP FIPAD PENTRU ZONE FIERBINTI SI CU
PRAF EURLEDA 1.2 40-840 ETDD SMC APC PA-U**

Reliability for hot and dusty conditions
Made in Europe housing, LED module and driver.
High resistance for demanding environments up to 50°C.
Wireless Bluetooth control available under request.
Downloads
Features
Mechanical
Housing Compressed fibreglass reinforced polyester (GRP), grey RAL 7035
Diffuser Injected polycarbonate with UV protection, opal finish
Gasket Polyurethane
Cable entry Grommet
Closing clips Polyamide 6 unremovable
Fixing clips Stainless steel
Operational Data
Light colour 4,000 K
CRI >80
Luminous flux 4,000 lm
Power 28 W
Efficiency 143 lm/W
Functional
Lifetime L70 50,000 h at 25°C
Fire protection PC / Flammability (UL94): V2
Glow wire test (EN 60695-2-11): 850°C|GRP / Flammability (UL94): HB
Glow wire test (EN 60695-2-11): 650°C
Electrical
Driver DALI dimmable
Power factor > 0.90 full load
Photometrical
Colour consistency < 3 SDCM
Dimensions
Length (X) 1,282 mm
Distance between springs (Xm) 800 mm
Width (Y) 145 mm
Height (Z) 101 mm
Weight 1.8 kg
<span class="elementor-button-text"
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/lampa-liniara-tip-fipad-pentru-zone-fierbinti-si-cu-praf-eurleda-1-2-40-840-etdd-smc-apc-pa-u-287633>