

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**ZALUX LAMPA LINIARA TIP FIPAD PENTRU ZONE FIERBINTI SI CU  
PRAF EURLEDA 1.5 56-865 ETDD SMC APC PA-U**

Reliability for hot and dusty conditions  
Made in Europe housing, LED module and driver.  
High resistance for demanding environments up to 50°C.  
Wireless Bluetooth control available under request.  
Downloads  
Features  
Mechanical  
Housing Compressed fibreglass reinforced polyester (GRP), grey RAL 7035  
Diffuser Injected polycarbonate with UV protection, opal finish  
Gasket Polyurethane  
Cable entry Grommet  
Closing clips Polyamide 6 unremovable  
Fixing clips Stainless steel  
Operational Data  
Light colour 6,500 K  
CRI >80  
Luminous flux 5,600 lm  
Power 40 W  
Efficiency 140 lm/W  
Functional  
Lifetime L70 50,000 h at 25°C  
Fire protection PC / Flammability (UL94): V2  
Glow wire test (EN 60695-2-11): 850°C|GRP / Flammability (UL94): HB  
Glow wire test (EN 60695-2-11): 650°C  
Electrical  
Driver DALI dimmable  
Power factor > 0.90 full load  
Photometrical  
Colour consistency < 3 SDCM  
Dimensions  
Length (X) 1,578 mm  
Distance between springs (Xm) 1,100 mm  
Width (Y) 145 mm  
Height (Z) 101 mm  
Weight 2.3 kg  
<span class="elementor-button-text"  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/lampa-liniara-tip-fipad-pentru-zone-fierbinti-si-cu-praf-eurleda-1-5-56-865-etdd-smc-apc-pa-u-287642>