


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**ZALUX LAMPA CILINDRICA PENTRU ILUMINARE ZONE EX , LAMPA
ATEX KRATEX HE 0.6 20-840 ET PC 3X2.5**

Connected lighting with a wide range of options for ATEX projects
Suitable for the hottest environments up to 55°C, even outdoors.
Compliant with gas groups IIA, IIB, IIC, due to its reduced MESH, making it perfect for
almost all ATEX environments.

DALI dimmable optional to optimize the use of the light and save energy.

Intelligent wireless control optional.

Downloads

Zone 1, 21

Ex II 2G Ex db IIC T6 Gb

Ex II 2D Ex tb IIIC T85 Db

Features

Mechanical

Profile UV resistant polycarbonate

End caps Aluminium alloy, yellow RAL 1003

Gasket NBR

Cable entry 2 entries of 3/4 NPT for cable gland (not included)

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 2,500 lm

Power 20 W

Efficiency 125 lm/W

Through wiring 3 x 2.5 mm²

Functional

Lifetime L80 50,000 h at 25°C

Fire protection PC / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 850°C

Electrical

Driver non dimmable

Connection 3 pole push wire terminal block

Flicker factor 5%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 750 mm

Distance between springs (Xm) 640 mm

Width (Y) 157 mm

Height (Z) 197 mm

Weight 5.7 kg

<span class="elementor-button-text"

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa-cilindrica-pentru-iluminare-zone-ex-lampa-atex-kratex-he-0-6-20-840-et-pc-3x2-5-287682>