

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **ZALUX CORP DE ILUMINAT REZISTENT IN MEDII CHIMICE PEM 158 LED-T8 C2 CG IX LM840**

Robust luminaire suitable for farming with high efficiency LED tube  
Up to 158lm/W.  
Safe against chemical elements and reliable for farming.  
Efficient LED tube made in glass to avoid deterioration and prevent sagging over time.  
Available in three lengths.  
Downloads  
Features  
Mechanical  
Housing Compressed fibreglass reinforced polyester (GRP), grey RAL 7035  
Diffuser Injected PMMA with UV protection, transparent finish  
Gasket Polyurethane  
Cable entry Cable gland  
Closing clips Stainless steel  
Fixing clips Stainless steel  
Operational Data  
Light colour 4,000 K  
CRI >80  
Luminous flux 3,800 lm  
Power 24 W  
Efficiency 158 lm/W  
Functional  
Lifetime L70 50,000 h at 25°C  
Fire protection GRP and PMMA / Flammability (UL94): HB  
Glow wire test (EN 60695-2-11): 650°C  
Electrical  
Driver non dimmable  
Connection 3 pole push wire terminal block  
Flicker factor < 8%  
Photometrical  
Dimensions  
Length (X) 1,575 mm  
Distance between springs (Xm) 1,140 mm  
Width (Y) 100 mm  
Height (Z) 108 mm  
Weight 2.1 kg  
<span class="elementor-button-text"  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-rezistent-in-medii-chimice-pem-158-led-t8-c2-cg-ix-lm840-287754>