

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**ZALUX CORP DE ILUMINAT REZISTENT IN MEDII CHIMICE PEM 218
LED-T8 C2 CG IX LM840**

Robust luminaire suitable for farming with high efficiency LED tube
Up to 158lm/W.
Safe against chemical elements and reliable for farming.
Efficient LED tube made in glass to avoid deterioration and prevent sagging over time.
Available in three lengths.
Downloads
Features
Mechanical
Housing Compressed fibreglass reinforced polyester (GRP), grey RAL 7035
Diffuser Injected PMMA with UV protection, transparent finish
Gasket Polyurethane
Cable entry Cable gland
Closing clips Stainless steel
Fixing clips Stainless steel
Operational Data
Light colour 4,000 K
CRI >80
Luminous flux 1,950 lm
Power 13 W
Efficiency 150 lm/W
Functional
Lifetime L70 50,000 h at 25°C
Fire protection GRP and PMMA / Flammability (UL94): HB
Glow wire test (EN 60695-2-11): 650°C
Electrical
Driver non dimmable
Connection 3 pole push wire terminal block
Flicker factor < 8%
Photometrical
Dimensions
Length (X) 666 mm
Distance between springs (Xm) 230 mm
Width (Y) 170 mm
Height (Z) 108 mm
Weight 1.4 kg
<span class="elementor-button-text"
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-rezistent-in-medii-chimice-pem-218-led-t8-c2-cg-ix-lm840-287758>