

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



ZALUX LAMPA PENTRU MEDII HIPERCLORURATE SI ÎN AER LIBER STRONGERTUBE G2 B 6500-840 ET HT PMMA ZB

For hyper chlorinated environments and outdoor
Specific potting for a full tight sealing to avoid the penetration of gases and water.
Safe against the corrosion of LED modules and electronic components.
High thickness PMMA resistant to chemicals and robust for a durable use in outdoor.
End caps with great thermal stability to resist UV radiation, heat, water, ageing and chemicals.

Downloads

Features

Mechanical

Profile High thickness PMMA

End caps Acrylonitrile styrene acrylate (ASA)

Gasket Polyurethane

Cable entry Cable gland with external cable

Fixing clips Specific stainless steel fixing brackets

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 6,500 lm

Power 43 W

Efficiency 150 lm/W

Functional

Lifetime L80 100,000 h at 35°C

Fire protection PMMA / Flammability (UL94): HB

Glow wire test (EN 60695-2-11): 650°C

Electrical

Driver non dimmable, high temperature

Connection 3 pole push wire terminal block

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,340 mm

Distance between springs (Xm) 1,205 mm

Width (Y) 112 mm

Height (Z) 112 mm

Weight 4.6 kg

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa-pentru-medii-hiperclorurate-si-in-aer-liber-strongertube-g2-b-6500-840-et-ht-pmma-zb-287795>