


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">ZALUX LAMPA IP66 IK12ZALED A EVOL G2 6000-840 ET PC</p> <p>High protection for indoor and outdoor applications Wide temperature range, suitable from cold storage to heavy industries. Excellent thermal management for use in tough environments. Safe for outdoor, with theft protection. Plug and play for tool-less, fast and easy installation.</p> <p>Downloads</p> <p>Features</p> <p>Mechanical</p> <p>Housing Die-cast aluminium alloy EN-47100, dark grey RAL DB703 Diffuser Injected polycarbonate with UV protection, opal finish Gasket Polyurethane Fixing clips Stainless steel</p> <p>Operational Data</p> <p>Light colour 4,000 K CRI >80 Luminous flux 6,000 lm Power 38 W Efficiency 158 lm/W</p> <p>Functional</p> <p>Lifetime L80 85,000 h at 35°C Fire protection PC / Flammability (UL94): V2 Glow wire test (EN 60695-2-11): 850°C</p> <p>Electrical</p> <p>Driver non dimmable Connection Stucchi Fast Connector Flicker factor < 1% Power factor > 0.95 full load</p> <p>Photometrical</p> <p>Colour consistency < 3 SDCM</p> <p>Dimensions</p> <p>Length (X) 1,047 mm Distance between springs (Xm) 492 mm Width (Y) 95 mm Height (Z) 105 mm Weight 2.9 kg</p> <p> Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/lampa-ip66-ik12zaleda-evol-g2-6000-840-et-pc-287864</p>
---	--