

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

**SCHNEIDER NEW UNICA - COVER FRAME + FIXING FRAME - 2 GS - 2
X 10 MODULES - ANTIBAC - WHITE**

Schneider Electric New Unica cover frame NU021020 is in color white. This cover frame has 2 gangs. It is made of thermoplastic ABS-UV stabilised, making it as resistant as possible. Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica System+ aesthetic group. What is more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 300 mm in width, 165 mm in height and 10 mm in depth. Besides, it is halogen free halogen free, which is good for your health. The device fixing mode is clip-in with 2 x 10 modules. And the product weighs 0.34 kg. Unica includes a suite of new designs, colors and materials. Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

range - New Unica
device application - Mounting
product or component type - Cover frame
aesthetic name - Unica System+
number of gangs - 2 gangs
installation direction - Horizontal
type of frame - Double
number of modules - 2 x 10 modules
fixing mode - Clip-in
colour tint - White (RAL 9003)
Complementary
provided equipment - Fixing frame
material - Thermoplastic ABS-UV stabilised: cover frame
surface treatment - Antibacterial
standards - IEC 60669-1
IEC 60884-1
width - 300 mm
height - 165 mm
depth - 10 mm
net weight - 0.34 kg
resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IK degree of protection - IK04
IP degree of protection - IP21D
Packing Units
Unit Type of Package 1 - PCE
Package 1 Length - 30.0 cm
Number of Units in Package 1 - 1
Package 3 Width - 18.0 cm
Package 3 Weight - 1.194 kg
Package 2 Width - 30.0 cm
Package 2 Height - 30.0 cm
Package 2 Weight - 5.228 kg
Number of Units in Package 3 - 3
Unit Type of Package 3 - BB1
Package 3 Height - 8.2 cm
Package 3 Length - 31.7 cm
Package 1 Width - 16.5 cm
Package 1 Height - 2.5 cm
Package 1 Weight - 356.0 g
Number of Units in Package 2 - 12
Unit Type of Package 2 - S03
Package 2 Length - 40.0 cm
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-cover-frame-fixing-frame-2-gs-2-x-10-modules-antibac-white-292518>