

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

**SCHNEIDER NEW UNICA - COVER FRAME + FIXING FRAME - 2  
GANGS - 2 X 10 MODULES - ALUMINIUM**

Schneider Electric New Unica cover frame NU021030 is in color aluminium This cover frame has 2 gangs. Being made of thermoplastic ABS-UV stabilised material, this cover frame is quite reliable and resistant. Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica System+ aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 300 mm in width, 165 mm in height and 10 mm in depth. Besides, it is halogen free halogen free, which is good for your health. The device's fixing mode is clip-in with 2 x 10 modules. And the product weighs 0.34 kg. Unica includes a suite of new designs, colors and materials. Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

range - New Unica  
device application - Mounting  
product or component type - Cover frame  
aesthetic name - Unica System+  
number of gangs - 2 gangs  
installation direction - Horizontal  
type of frame - Double  
number of modules - 2 x 10 modules  
fixing mode - Clip-in  
colour tint - Aluminium  
Complementary  
provided equipment - Fixing frame  
material - Thermoplastic ABS-UV stabilised: cover frame  
standards - IEC 60669-1  
IEC 60884-1  
width - 300 mm  
height - 165 mm  
depth - 10 mm  
net weight - 0.34 kg  
resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IK degree of protection - IK04  
IP degree of protection - IP21D  
Packing Units  
Unit Type of Package 1 - PCE  
Package 1 Length - 30.0 cm  
Number of Units in Package 1 - 1  
Package 2 Width - 30 cm  
Package 2 Height - 15 cm  
Package 2 Weight - 1.52 kg  
Package 3 Height - 77 cm  
Package 1 Width - 16.5 cm  
Package 1 Height - 1.0 cm  
Package 1 Weight - 361.0 g  
Number of Units in Package 2 - 3  
Unit Type of Package 2 - S02  
Package 2 Length - 40 cm  
arrow2\_down  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-cover-frame-fixing-frame-2-gangs-2-x-10-modules-aluminium-292519>