

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

**SCHNEIDER NEW UNICA - COVER FRAME + FIXING FRAME - 2
GANGS - 2 X 8 MODULES - ALUMINIUM**

Schneider Electric New Unica cover frame NU021830 is in color aluminium. The cover frame is made of thermoplastic ABS-UV stabilised, making it as resistant as possible. This cover frame has 2 gangs. Besides, it reaches IK04 protection level, which can help protect against impact. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica System+ aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 230 mm in width. 165 mm in height. 10 mm in depth. Besides it is halogen free, which is good for your health. The device's fixing mode is clip-in with 2 x 8 modules. And the product weighs 0.261 kg. Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

range - New Unica
device application - Mounting
product or component type - Cover frame
aesthetic name - Unica System+
number of gangs - 2 gangs
installation direction - Horizontal
type of frame - Double
number of modules - 2 x 8 modules
fixing mode - Clip-in
colour tint - Aluminium
Complementary
provided equipment - Fixing frame
material - Thermoplastic ABS-UV stabilised: cover frame
standards - IEC 60669-1
IEC 60884-1
width - 230 mm
height - 165 mm
depth - 10 mm
net weight - 0.261 kg
resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IK degree of protection - IK04
IP degree of protection - IP21D
Packing Units
Unit Type of Package 1 - PCE
Package 1 Length - 23.0 cm
Number of Units in Package 1 - 1
Package 3 Width - 18.0 cm
Package 3 Weight - 910.0 g
Package 2 Width - 30.0 cm
Package 2 Height - 30.0 cm
Package 2 Weight - 5.859 kg
Number of Units in Package 3 - 3
Unit Type of Package 3 - BB1
Package 3 Height - 8.0 cm
Package 3 Length - 25.0 cm
Package 1 Width - 16.5 cm
Package 1 Height - 1.0 cm
Package 1 Weight - 268.0 g
Number of Units in Package 2 - 18
Unit Type of Package 2 - S03
Package 2 Length - 40.0 cm
arrow2_down
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-cover-frame-fixing-frame-2-gangs-2-x-8-modules-aluminium-292970>