

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK SIGURANTA AUTOMATA VA47-60MA FARA RELEU TERMIC 1P 16A 6KA D

Modular circuit breakers (MCB) without thermal protection designed for system protection against short circuit currents. Used on facilities with emergency ventilation and fire extinguishing systems. Range of use: - distribution switchboards; - low-voltage switches; - distribution panels. Electromagnetic protection against overcurrent. Wide handle for easy switching on/off of circuit breaker.

Latch on DIN rack with double fixed position.

The notches on the contact clamps reduce the heat loss and increase the mechanical strength of the joint.

Wide range of operating temperatures from -40 °C to + 50 ° C. Number of poles: 1

Primary current: 16

Release characteristic: EV000413

Nominal operating voltage: 230/400

Rated short-circuit breaking capacity EN 60898: 6

Width in number of modular spacings: 1

Max. cross section incoming cable: 25

Rated surge voltage invariability: 6

Frequency: 50

Frequency: 50

Degree of protection (IP): EV006405

Switch off technique: EV021689

Mechanical wear resistance: > 20000

Electric wear resistance: > 8000

Weight of one pole: ≤ 0,1

Number of poles (total): 1

Voltage type: EV000460

Type of electric connection: EV000415

Nominal rated current: 16.0

Nominal rated voltage: 230

Number of protected poles: 1

Ambient temperature during operating: -40...+50

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/siguranta-automata-va47-60ma-fara-releu-termic-1p-16a-6ka-d-306737>