

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK SIGURANTA AUTOMATA VA47-150 3P 100A 15KA CURBA C

Modular circuit breakers (MCB) VA47-150 are designed to protect distribution and group circuits from high short-circuit currents. They are recommended for use in input and distribution devices of household and industrial electrical installations. Ultimate breaking capacity is 15000 A. 32 standard versions for 4 rated currents. Current curve characteristics C and D Overcurrent protection at each pole.

Quick installation and additional fastening reliability.

Ergonomic handle design.

Logo engraving on the side.

Notches on the contact clamps increase the mechanical stability of the joint.

Main circuit status indicator. Number of poles: 3

Primary current: 100

Release characteristic: EV000084

Nominal operating voltage: 400

Rated short-circuit breaking capacity EN 60898: 15

Width in number of modular spacings: 4,5

Max. cross section incoming cable: 50

Rated surge voltage invariability: 6

Frequency: 50

Frequency: 50

Degree of protection (IP): EV006415

Ambient class: IEK_V000010

Mechanical wear resistance: ≥ 6000

Electric wear resistance: ≥ 4000

Weight of one pole: 0,194

Number of poles (total): 3

Voltage type: EV000460

Type of electric connection: EV000415

Mounting rail type: IEK_V0000516

Operation mode: IEK_V0000273

Maintainability: EV000494

Nominal rated current: 100.0

Nominal rated voltage: 400

Number of protected poles: 3

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/siguranta-automata-va47-150-3p-100a-15ka-curba-c-306865>